

# PDS series

## Easy-to-use digital switchers



The PDS series is designed to meet today's requirements for a high-quality, easy-to-use and fast seamless switcher with more digital inputs at an affordable price. The PDS is offered in three models: PDS-701 3G, PDS-901 3G and PDS-902 3G. Thanks to its straightforward setup and operation the PDS is a perfect fit for live events, boardrooms, hotel ballrooms, houses of worship, education and training facilities and fixed installations.

### Three models

The PDS-901 3G and PDS-902 3G models feature four DVI-I inputs with full HDCP 1.0 support, whereas the PDS-701 3G features two DVI-I inputs. All models include one 3G/HD/SD SDI and four universal analog inputs. All analog and DVI inputs support the EDID 1.3 specification. Users can capture and store up to three images that can be used as a LOGO source during the presentation. Built-in test patterns are also provided.

### Program output

All models offer simultaneous program output via the DVI and analog connectors. The PDS-902 3G and PDS-901 3G models also include an SDI output supporting SD/HD/3G rates and BarcoLink for easy connection to your Barco projectors. In addition, the PDS-902 3G offers a preview output that can be set at different resolution than the program output. Users have the option of displaying one of three signals on the preview output: program, preview or test pattern.

The PDS series won a Commercial Integrator BEST Award at InfoComm 2013.

**BARCO**

Visibly yours

## Product specifications

## PDS series

<b>Video inputs</b>																									
<b>DVI-I</b>	<ul style="list-style-type: none"> <li>■ Digital formats: all single-link DVI digital formats up to 165 Mhz, per DVI 1.0 specification</li> <li>■ Analog formats: NTSC/PAL composite and Y/C video, SD YPbPr with bi-level sync, HD YPbPr with tri-level sync, RGBHV/RGBS/RGSB computer video with bi-level sync</li> <li>■ Analog 1:1 sampling up to 1920x1080@60 Hz. Sources with native pixel rates greater than 150 MHz will be filtered and sampled at 150 Mhz. These include but not limited to 1920x1080p@60 (173.0 MHz), 1920x1200@60 (193.25 MHz) and 2048x1080p@60 (183.75 MHz)</li> <li>■ EDID version 1.3 compatible - HDCP version 1.0 compatible</li> </ul>																								
<b>HD-15 VGA</b>	<ul style="list-style-type: none"> <li>■ Format: NTSC/PAL composite with Y/C video SD YPbPr with bi-level sync HD YPbPr with tri-level sync per SMPTE 274, RGBHV/RGBS/RGSB computer video with bi-level sync</li> <li>■ Analog 1:1 sampling up to 1920x1080@60 Hz. Sources with native pixel rates greater than 150 MHz will be filtered and sampled at 150 Mhz. These include but not limited to 1920x1080p@60 (173.0 MHz), 1920x1200@60 (193.25 MHz) and 2048x1080p@60 (183.75 MHz)</li> <li>■ EDID version 1.3 compatible</li> </ul>																								
<b>SD-HD-3G SDI on BNC</b>	Formats: SD-SDI per SMPTE 259M-C (NTSC/PAL resolution); HD-SDI per SMPTE 292M, 296M; 3G-SDI per SMTE 424M; BarcoLink																								
<b>Video outputs</b>																									
<b>DVI-I</b>	<ul style="list-style-type: none"> <li>■ Formats: all single-link DVI digital formats up to 165 Mhz, per DVI 1.0 spec</li> <li>■ EDID version 1.3 compatible - HDCP version 1.0 compatible</li> </ul>																								
<b>HD-15 VGA</b>	<ul style="list-style-type: none"> <li>■ Formats: HD YPbPr with tri-level sync per SMPTE 274, RGBHV/RGBS/RGSB computer video with bi-level sync</li> <li>■ EDID version 1.3 compatible</li> </ul>																								
<b>SD-HD-3G SDI on BNC</b>	Formats: SD-SDI per SMPTE 259M-C (NTSC/PAL resolution); HD-SDI per SMPTE 292M, 296M; 3G-SDI per SMPTE 424M; BarcoLink																								
<b>Other</b>																									
<b>Control</b>	<ul style="list-style-type: none"> <li>■ Ethernet RJ-45, 10/100 Mbps autosense</li> <li>■ computer, tablet, smartphone, or Encore or ScreenPRO-II controller via Ethernet link</li> </ul>																								
<b>Height</b>	1.75 inches (4.4 cm) - 1 RU rackmount																								
<b>Width</b>	17 inches (43.2 cm) without chassis handles, 19.06 inches (48.4 cm) with chassis handles attached																								
<b>Depth</b>	14.25 inches (36.2 cm) from front to rear panel																								
<b>Weight</b>	12.5 lbs - 5.67 kg																								
<b>Input power</b>	100-240 VAC, 47-63 Hz, auto-selecting 2.0 A maximum																								
<b>Environmental</b>	Humidity: 0-95% non-condensing																								
<b>Temperature</b>	0-40°C																								
<b>Warranty</b>	Full three-year parts and labor warranty																								
<b>Available models</b>																									
<b>Three digital switchers</b>	<table border="1"> <thead> <tr> <th></th> <th>VGA-inputs</th> <th>DVI-I inputs</th> <th>3G SDI inputs</th> <th>Program output</th> <th>Preview output</th> </tr> </thead> <tbody> <tr> <td><b>PDS-701 3G</b></td> <td>4</td> <td>2</td> <td>1</td> <td>1</td> <td>-</td> </tr> <tr> <td><b>PDS-901 3G</b></td> <td>4</td> <td>4</td> <td>1</td> <td>1</td> <td>-</td> </tr> <tr> <td><b>PDS-902 3G</b></td> <td>4</td> <td>4</td> <td>1</td> <td>1</td> <td>1</td> </tr> </tbody> </table>		VGA-inputs	DVI-I inputs	3G SDI inputs	Program output	Preview output	<b>PDS-701 3G</b>	4	2	1	1	-	<b>PDS-901 3G</b>	4	4	1	1	-	<b>PDS-902 3G</b>	4	4	1	1	1
	VGA-inputs	DVI-I inputs	3G SDI inputs	Program output	Preview output																				
<b>PDS-701 3G</b>	4	2	1	1	-																				
<b>PDS-901 3G</b>	4	4	1	1	-																				
<b>PDS-902 3G</b>	4	4	1	1	1																				

Last updated: 12 jun 2014  
 Technical specifications are subject to change without prior notice.  
 Please check [www.barco.com](http://www.barco.com) for the latest information.