

**Series Name**

DM-E Series

Display**Screen Size**

65

Panel Technology

60Hz D-LED BLU

Resolution

1920x1080

Aspect Ratio

16:9

Brightness

450

Contrast Ratio (Typical)

4000:1

Contrast Ratio (Dynamic)

N/A

Viewing Angle (H/V)

178:178

Response Time

6.5ms

Connectivity**Input**

Analog D-SUB, DVI-D(HDMI Common), Display Port 1.2, HDMI1, HDMI2 (thru DVI-D Input, Adapter Not Included) Component(CVBS Common),Stereo mini Jack, USB 2.0 x 1

Output

DP1.2(Loop-out), Stereo mini Jack

External Control

RS232C (In/Out) thru Stereo Jack, RJ45

Sensor

IR, Ambient Light

Power**Power Supply**

AC 100 - 240 V~ (+/- 10 %), 50/60 Hz

Power Consumption (Typical/Max)

110W / 264W

Power Consumption (Standby)

< 0.5W



Environmental Conditions	Multimedia Speakers
	N/A
Operating Temperature	Plug & Play
0°~ 40°	N/A
Operating Humidity	Pre-Installed
10~80%	N/A
Special	24/7 Operation
Hardware: Super Clear Coating, Temperature Sensor, Video Wall(15x15), Pivot Display, Clock Battery(168hrs Clock Keeping), Built in Speaker(10W x 2), WiFi Module Embedded, SD Card Slot	Yes
Software: Magic Clone(to USB), Auto Source Switching & Recovery, RS232C/RJ45 MDC, Plug and Play, PIP/PBP, Image Rotation, Button Lock, DP 1.2 Digital Daisy Chain(HDCP Support), Built In MagicInfo Player S2, Firmware Update by Network, LFD New Home Screen, PC-less VideoWall, Predefined Template for Vertical Usage, Multi Channel, Mobile Control, Event Schedule, Backup Player, PC-less Touch, MagicPresenter“	Wi-Fi
	Yes
	VideoWall/Thin Bezel
	N/A
	Built-in Speakers
	10W + 10W
SMART Signage Platform	Outdoor
Yes	N/A
Built-in Tuner	Storage
Yes	8GB
Media Player Type	Dimensions
SBB(Optional), PIM(Optional)	
VESA Standard Wall-Mount Interface	Without Stand (W x H x D)
N/A	57.8“ x 33.4“ x 2.2“
Touchscreen	Packaging (W x H x D)
N/A	63“ x 38.6“ x 8.5“
	Bezel Width



18.0mm (Top/Side), 23.5mm (Bottom)

Weight

Product Weight

60.4 lb.

Package Weight

78 lb.

Service

Standard Warranty

3 years onsite parts/labor

Included in Box

Included in Box

Quick Setup Guide, Regulatory Guide, Warranty Card, D-Sub cable, Power Cord, Remote Controller, Batteries, RS232C(IN) adapter, COVER-JACK

Optional Wall Mount Kit

WMN4675MD, WMN4277SD, WMN6575SD

Optional Stand

STN-L6500E

Optional Touch Overlay

N/A

Welcome Board

N/A

Interlocking Kit with Base Stand

N/A

Dummy Stand for Interlocking Kits

N/A

Ext. BR/R Sensor

N/A

Tuner Card

N/A

Optional Media Player

SBB (Optional), PIM (Optional)

Plug in Module

N/A

USB

N/A

Green Management

ENERGY STAR® Certified

N/A

RoHS Compliant

N/A

Emission Standard

N/A

Packaging Recyclability

N/A

Mechanical Specs

VESA Mount

400 x 400mm