

**Series Name**

ME-C

Display**Screen Size**

40"

Panel Technology

60Hz (Edge-LED Backlight)

Resolution

1920 x 1080

Brightness

450 nits

Contrast Ratio (Typical)

5000:1

Viewing Angle (H/V)

178°/178°

Response Time

8ms

Connectivity**Input**

VGA (D-Sub 15 Pin), DVI-D (In/Out), 2 HDMI, DisplayPort 1.2, Component (CVBS Common), USB, Stereo Mini Jack, TV in

Output

DisplayPort 1.2 (Loop-Out), Stereo Mini Jack

**External Control**

RJ45, RS232C (In/Out) thru stereo jack

Sensor

IR/Ambient Light

Power**Power Supply**

AC 100 - 240 V~ (+/- 10 %), 50/60 Hz

Power Consumption (Typical/Max)

93W / 110W

Power Consumption (Standby)

<0.5W

Environmental Conditions**Operating Temperature**

0° - 40°

Operating Humidity

10 - 80%



Features

Special

Magic Clone (to USB), Auto Source Switching & Recovery, Lamp Error Detection, Super Clear Coating, Temperature Sensor, Plug and Play (DDC2B), Pivot Display, Clock Battery, PIP/PBP, Video Wall (10 x 10), Image Rotation, Button Lock, HDCP Support, Smart Scheduling, Smart F/W Update, Built-In MagicInfo Premium-S

SMART Signage Platform

Yes

Built-in Tuner

Yes

Media Player Type

Cortex-A9 1 GHz Dual Core, 1 GB DDR3, 4GB FDM, USB (2)

VESA Standard Wall-Mount Interface

200 x 200mm

Built-in Speakers

Yes

Dimensions

Without Stand (W x H x D)

36.3" x 21.2" x 1.2"

Packaging (W x H x D)

40.2" x 24.3" x 5.1"

Bezel Width

16.2mm (Bottom 20.9mm)

Weight

Product Weight

23.4 lb.

Package Weight

27.8 lb.

Service

Standard Warranty

3-Year On-Site (Parts/Labor)

Included in Box

Included in Box

Quick Setup Guide, Warranty Card, Application CD, D-Sub Cable, Power Cord, Remote Controller, Batteries

Optional Wall Mount Kit

WMN4070SD

WMN250MD

Optional Stand

STN-L4055AD

Optional Touch Overlay

CY-TM40LCA

Optional Media Player

SBB-C, SBB-CD7, SBB-CQ7